

MVH point drain **P7** with all-round sealing-on web

The reliable connection of the underground car park coating to the drains is one of the main criteria for the avoidance of damage to the building fabric by chlorides penetrating into the concrete. The MVH trough P5 provides this possibility by means of an all-round 50 mm wide sealing-on web.

The height of the web depends on the thickness of the coating applied. A special adhesive system developed by MVH GmbH produces, by means of a rough surface, optimum hold of the coating on the stainless steel sealing web.



All-round sealing-on web, 50 mm wide to take up the coating



Drainage nozzle vertical / horizontal. DN 70 / DN 100. Length corresponding to the thickness of the roof of the underground car park.

MVH point drain with all-round sealing-on web



System features

- Material:** Stainless steel V4A, materials 1.4571 or 1.4404.
- Material thickness:** Drain 2 mm.
- Surface finish:** Pickled in immersion bath. Sand blasting and electrolytic polishing on request.
- Outer dimensions:** 200 x 200 mm, 300 x 300 mm. Special dimensions possible on request
- Connection possibility:** Drainage nozzle DN 70 or DN 100. Vertical or horizontal.
- Covers:** Standard grating mesh width 30/10, screw connected safe for traffic. Other mesh widths possible.

Type P7

Drain bottom part, outer dimensions 200 x 200 mm	Article No. 11071001
Grating MW 30/10, length 185 x 185 mm	Article No. 11087001
Drainage nozzle, DN 100	Article No. 17007051
Drainage nozzle, DN 70	Article No. 17007051
Drain bottom part, outer dimensions 300 x 300 mm	Article No. 11071002
Grating MW 30/10, length 285x285 mm	Article No. 11087002
Drainage nozzle DN 100	Article No. 17007050
Drainage nozzle DN 70	Article No. 17007051